




#### Installation Method



Monolithic

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).

**Product** Touch & Tones II 103 **Colour** Blush **Collection** Touch & Tones II Collection  
**Backing** CQuest™Bio

#### Product Specifications

Product Construction	Tufted Plain Shag Cut Pile
Yarn System	100% Recycled Nylon
Standard Backing	CQuest™Bio
Size	50cm x 50cm
Tiles per Box	12 - 3m <sup>2</sup>

#### More Product Specifications

Pile Yarn Weight	1,136 g/m <sup>2</sup> ± 5%
Total Weight	4,318 g/m <sup>2</sup> ± 5%
Pile Height	7.1 mm +15% / - 10%
Total Thickness	10.4 mm ±0.5mm
Gauge - Ends per 10 cm	5/16 - 12.6
Tufts per m <sup>2</sup>	42840 /m <sup>2</sup> ±5%

#### Performance Specifications















Wear Classification	EN 1307 33 Heavy Contract
Castor Chair Rating	≥2.4 (EN 985) Continuous Use
Flammability	(EN ISO 9239-1: 2010) Euroclass Bfl-s1 (EN 13501-1)
Light Fastness	≥5 (ISO 105-B02)
Light Reflectance Value (LRV-L)	52.42
Light Reflectance Value (LRV-Y)	20.52
Dimensional Stability	≤0.2% (ISO 2551/EN 986)
Impact Sound	25 dB
Insulation ΔLw EN ISO 10140-3	
Rating of Sound Absorption (αw) EN ISO 11654	0.2
Sound Absorption (αs)EN ISO 354 at 125 Hz	0.02
Sound Absorption (αs)EN ISO 354 at 250 Hz	0.07
Sound Absorption (αs)EN ISO 354 at 500 Hz	0.12
Sound Absorption (αs)EN ISO 354 at 1000 Hz	0.27
Sound Absorption (αs)EN ISO 354 at 2000 Hz	0.41
Sound Absorption (αs)EN ISO 354 at 4000 Hz	0.56

#### Environmental Specifications

Environmental Product Declaration	<a href="#">Download EPD</a>
Disclosure of Product Ingredients	<a href="#">Health Product Declaration</a>
Total Recycled Content	79.1 %
Pre-Consumer (Total)	65.90 %
Post-Consumer (Total)	13.20 %
Yarn Recycled Content	100.00 %
Pre-Consumer (Yarn)	50.00 %
Post-Consumer (Yarn)	50.00 %
Total Bio Based Content	8.8 %
Total Recycled & Bio Based Content	87.9 %
Indoor Air Quality	<a href="#">Compliant with LEED EQ 5.0 credit</a> French A+ GLP 100254 M1 Emission Certification -CQB

HQE (France)	<a href="#">View Potential HQE Contribution</a>
DGNB (Germany)	<a href="#">View Potential DGNB Contribution</a>
Embodied Carbon (Cradle to Gate)	4.58 kg CO <sub>2</sub> eq./m <sup>2</sup>
Environmental Certifications	<a href="#">Cradle to Cradle Certified® v3.1 Silver</a>
Installation Waste	Monolithic - 3-4%
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Waste to Energy	Can be incinerated in appropriate waste to energy plant.
<b>Technical Information</b>	
Installation	<a href="#">See recommended Interface installation guidelines</a>
Maintenance	<a href="#">See recommended Interface maintenance guidelines</a>
Warranty	15 years
Manufacturing Location	<a href="#">ISO 9001, 14001 &amp; 45001 Certified Facilities in Europe</a>

### Certifications

	 DOP: 1037/128289 EN 14041:2004 Notified Body: 0493 COC 0493 - CPR - 0181 For use as floor covering in buildings	 DOP: 1037/128289 EN 14041:2004 Approved Body: 5515 COC 8515/CPR/0181 For use as floor covering in buildings			
 >0,30	 <2,0 kV	 25 dB	 0,2	 ≥ 5	
 0.108	 ≥2.4	