


# Macaw & Macaw Stripe


## Loop Pile Carpet Tiles



<b>Style</b> (Méthode de fabrication/ Herstellungsverfahren/ Descripción)	Tufted 1/10" Gauge Loop Pile Tile
<b>Yarn Construction</b> (Couche d'usure/ Polmaterial/ Composición fibra)	100% Solution Dyed Polypropylene
<b>Total Recycled Content</b> (Contenu recyclé total/ Gesamtrecyclinganteil/ Contenido total reciclado)	66%
<b>Pile Yarn Weight</b> (Poids du velours/ Poleinsatzgewicht/ Peso fibra)	420g/m <sup>2</sup>
<b>Pile Height</b> (Épaisseur du velours/ Polhöhe/ Altura fibra)	3.5mm
<b>Total Weight</b> (Poids total/ Gesamtgewicht/ Peso total)	4210g/m <sup>2</sup>
<b>Total Thickness</b> (Épaisseur totale/ Gesamtdicke/ Espesor total)	6mm
<b>Backing</b> (Dossier standard/ Standardrückenausstattung/ Tipo de base)	100% Envirobase - minimum of 75% recycled material
<b>Additional Acoustic Backing</b> (Dossier acoustique supplémentaire/ Zusätzliche Akustikrückenausstattung/ Respaldo acústico adicional)	Komfort Bac available on request
<b>Tile Size</b> (Dimension / Abmessung / Tamaño)	50cm x 50cm
<b>Tiles Per Box</b> (Emballage / Verpackung / Embalaje)	20 (5m <sup>2</sup> )
<b>Wear Classification</b> (Classement d'usage/ Beanspruchungsbereich/ Clasificación al tráfico)	General Contract
<b>Luxury Class</b> (Classement de confort/ Komfortklasse/ Clase de lujo)	LC1
<b>Anti-Static Behaviour</b> (Antistatique/ Antistatisch/ Comportamiento antiestático)	Suitable for use with computers. Less than 2Kv
<b>Colour Fastness (Light)</b> (Solidité des couleurs à la lumière/ Lichtechtheit/ Resistencia a la luz solar)	BS EN ISO 105:B02 >6
<b>Colour Fastness (Shampoo)</b> (Solidité des couleurs au shampooing/ Farbechtheit (Shamponieren/ Resistencia de los colores al champú)	BS 1006:UK-TB:1990 4-5
<b>Colour Fastness (Dry Rubbing)</b> (Solidité des couleurs au frottement à sec/ Reibechtheit (Trocken)/ Solidez al frote (seco)	BS EN ISO 105:B01 4-5
<b>Colour Fastness (Wet Rubbing)</b> (Solidité au frottement au mouillé/ Reibechtheit (Nass)/ Solidez al frote (mojado)	BS EN ISO 105:X12 4-5
<b>Flammability BS 4790</b> Hot Metal Test (Tenue au feu/ Brandverhalten/ Inflamabilidad)	BS5287 Assessment and labelling of Textile Floorcovering tested to BS4790 (Hot Metal Nut Test) - Low Radius of Char
<b>Flammability- BS EN 13501</b> (Tenue au feu/ Brandverhalten/ Inflamabilidad)	Class Efl
<b>Impact Sound</b> (Réduction du bruit d'impact/ Trittschallverbesserungsmaß/ Aislamiento a los ruidos de impactos)	22dB
<b>VOC Content</b> (Contenu en COV/ VOC-Gehalt/ Contenido de COV)	E1 in relation to EN 14041:2004



**Broadloom**  
Macaw can be laid broadloom



**Tessellated**  
Macaw & Macaw Stripe can be laid tessellated

Please note, for technical reasons, as with all textile materials, it is not possible to colour match from different batches. Orders that need to colour match should be placed at the same time. Production may, therefore, show variations to the sample card. Paragon Carpet Tiles reserves the right to change or modify product specifications without giving prior notice.



**To place your order**  
+44 (0)1709 763800 | sales@paragon-carpets.co.uk

**More information & samples**  
paragon-carpets.co.uk | samples@paragon-carpets.co.uk

**Paragon Carpet Tiles**  
Farfield Park, Manvers,  
Wath-upon-Dearne,  
Rotherham, S63 5DB,  
United Kingdom

