

Sunex



Furlong Flooring®
First choice flooring for every room

Product Specification

PRODUCT INFORMATION		PRODUCT SPECIFICATION	
Collection		Sunex	
Type		Laminate	
Dimensions		1205mm (L) x 197mm(W)	EN 13329 +A1
Thickness		8mm	EN 13329+A1
Packaging -Piece		10 pieces / 1 package	
M ²		2.374 m ²	
KG		16kg	
Pallet -Piece		48 Package / 1 Pallet	
M ²		142,44 m ²	
KG		975kg	
Class		31	EN 13329 +A1
Abrasion resistance		AC3	EN 13329 +A1
Thickness swelling %		≤18	ISO 24336
Resistance to Impact	Small Ball N	≥8	EN 13329 +A1
Large Ball mm		≥500	
Warranty Domestic/Commercial		10/5	
Resistance to Staining		Min5 (group 1 & 2) Min.4 (group 3)	EN 438-2_5
Surface Soundness	N/mm ²	≥1.0	EN 13329+A1
Lock Strength L/W	kN/m	-	ISO 24334
Effect of Castor Chair	25.000 cycles	No damage	EN 425:2002
Effect of Furniture Leg		No damage	EN 424
Opening between Elements		≤0,20	EN 13329 +A1
Height difference between elements		≤0,15	EN13329+A1
Moisture Content %		4-10	EN 322
Fire Resistance Class		C _{fl} S1	EN 923-1





Sunex

Product Specification

Sustainably sourced with a Uniclic® system for faster fitting, Sunex delivers on price, quality and aesthetic. This 8mm thick range consists of 4 plank decors and has a 24 hours water resistance.

COLOURS	CODE
Jawa	A72366
Malaga	A72367
Merida	A72369
Muson	A72368

24hrs Water Resistant

Eco-Friendly

Click Fitting

Sustainably Sourced

10 YEAR
Wear and Stain Warranty