

Installation Method



Ashlar

Brick

Monolithic

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Works Flow **Colour** Pebble **Collection** Works Collection **Backing** CQuest™Bio

Product Specifications

Product Construction	Tufted Patterned Structured Loop Pile
Yarn System	100% Solution Dyed Nylon
Standard Backing	CQuest™Bio
Size	50cm x 50cm
Tiles per Box	16 - 4m ²
Optional Backings	CQuest™Bio SONE

More Product Specifications

Pile Yarn Weight	600 g/m ² ± 5%
Total Weight	3,980 g/m ² ± 5%
Pile Height	3.3 mm +15% / - 10%
Total Thickness	6.6 mm ±0.5mm
Gauge - Ends per 10 cm	1/12 - 47.2
Tufts per m ²	165200 /m ² ±5%

Performance Specifications

















Wear Classification	EN 1307 33 Heavy Contract
Castor Chair Rating	≥2.4 (EN 985) Continuous Use
Flammability	(EN ISO 9239-1: 2010) Euroclass Bfl-s1 (EN 13501-1)
Light Fastness	≥7 (ISO 105-B02)
Light Reflectance Value (LRV-L)	40.80
Light Reflectance Value (LRV-Y)	11.70
Dimensional Stability	≤0.2% (ISO 2551/EN 986)
Impact Sound Insulation ΔLw EN ISO 10140-3	23 dB
Rating of Sound Absorption (αw) EN ISO 11654	0.2
Sound Absorption (αs) EN ISO 354 at 125 Hz	0.04
Sound Absorption (αs) EN ISO 354 at 250 Hz	0.02
Sound Absorption (αs) EN ISO 354 at 500 Hz	0.08
Sound Absorption (αs) EN ISO 354 at 1000 Hz	0.19
Sound Absorption (αs) EN ISO 354 at 2000 Hz	0.34
Sound Absorption (αs) EN ISO 354 at 4000 Hz	0.43

Environmental Specifications

Environmental Product Declaration	Download EPD
Disclosure of Product Ingredients	Health Product Declaration
Total Recycled Content	62.9 %
Pre-Consumer (Total)	62.90 %
Total Bio Based Content	9.52 %
Total Recycled & Bio Based Content	72.42 %
Indoor Air Quality	Compliant with LEED EQ 5.0 credit French A+ GLP 100209 M1 Emission Certification -CQB
HQE (France)	View Potential HQE Contribution
DGNB (Germany)	View Potential DGNB Contribution
Embodied Carbon (Cradle to Gate)	5.63 kg CO ₂ eq./m ²

Installation Waste	Ashlar – 3-5 % Monolithic – 3-4% Brick – 3-5 %
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Waste to Energy	Can be incinerated in appropriate waste to energy plant.
Technical Information	
Installation	See recommended Interface installation guidelines
Maintenance	See recommended Interface maintenance guidelines
Warranty	15 years
Manufacturing Location	ISO 9001, 14001 & 45001 Certified Facilities in Europe

Certifications

 DOP: 1039/127357 EN 14041:2004 Notified Body - 0403 COC 0493- CPR- 0181 For use as floor covering in buildings	 DOP: 1039/127357 EN 14041:2004 Approved Body - 8515 COC 8515/CPR/0181 For use as floor covering in buildings			 L B ₁ -s1 NCS	 >0,30
 <2.0 kV	 <10 ⁹ Ω	 23 dB	 0.2	 ≥ 7	
 0.07	 ≥2.4		 EMISSIOM DANS L'AIR INTERIEUR A+ A B C	